

University of Nebraska - Lincoln

DigitalCommons@University of Nebraska - Lincoln

Nebraska Tractor Tests

Tractor Test and Power Museum, The Lester F. Larsen

2003

Nebraska Summary S303A: Challenger MT 535

Nebraska Tractor Test Laboratory

University of Nebraska-Lincoln, tractortestlab@unl.edu

Follow this and additional works at: <https://digitalcommons.unl.edu/tractormuseumlit>



Part of the [Energy Systems Commons](#), [History of Science, Technology, and Medicine Commons](#), [Other Mechanical Engineering Commons](#), [Physical Sciences and Mathematics Commons](#), [Science and Mathematics Education Commons](#), and the [United States History Commons](#)

Laboratory, Nebraska Tractor Test, "Nebraska Summary S303A: Challenger MT 535" (2003). *Nebraska Tractor Tests*. 3465.

<https://digitalcommons.unl.edu/tractormuseumlit/3465>

This Article is brought to you for free and open access by the Tractor Test and Power Museum, The Lester F. Larsen at DigitalCommons@University of Nebraska - Lincoln. It has been accepted for inclusion in Nebraska Tractor Tests by an authorized administrator of DigitalCommons@University of Nebraska - Lincoln.

SUMMARY OF OECD TESTS 1860 & 1861-NEBRASKA SUMMARY 303A

CHALLENGER MT 535 DIESEL

32 SPEED

POWER TAKE-OFF PERFORMANCE

Power HP (kW)	Crank shaft speed rpm	Gal/hr (l/h)	lb/hp.hr (kg/kW.h)	Hp.hr/gal (kW.h/l)	Mean Atmospheric Conditions
MAXIMUM POWER AND FUEL CONSUMPTION					
Rated Engine Speed—(PTO speed—1090 rpm)					
100.2 (74.7)	2180	6.08 (23.00)	0.431 (0.262)	16.49 (3.25)	
Maximum Power (2 Hours)					
103.9 (77.5)	2030	5.93 (22.46)	0.406 (0.247)	17.51 (3.45)	
Standard Power Take-off Speed (1000 rpm)					
103.5 (77.2)	2000	5.85 (22.15)	0.401 (0.244)	17.69 (3.49)	

VARYING POWER AND FUEL CONSUMPTION

100.2 (74.7)	2180	6.08 (23.00)	0.431 (0.262)	16.49 (3.25)	Air temperature
87.8 (65.5)	2227	5.59 (21.18)	0.452 (0.275)	15.70 (3.09)	64°F (18°C)
66.4 (49.5)	2251	4.82 (18.26)	0.515 (0.314)	13.78 (2.71)	Relative humidity
44.4 (33.1)	2268	3.95 (14.95)	0.632 (0.384)	11.24 (2.21)	40%
22.3 (16.6)	2281	2.84 (10.76)	0.906 (0.551)	7.84 (1.54)	Barometer
--	2296	1.89 (7.17)	--	--	29.7" Hg (100.7 kPa)

Maximum Torque - 316.1 lb.-ft. (428.6 Nm) at 1120 rpm

Maximum Torque rise - 30.5%

Torque rise at 1800 engine rpm - 21%

DRAWBAR PERFORMANCE (Unballasted - Front Drive Engaged) FUEL CONSUMPTION CHARACTERISTICS

Power Hp (kW)	Drawbar pull lbs (kN)	Speed mph (km/h)	Crank- shaft speed rpm	Slip %	Fuel Consumption lb/hp.hr (kg/kW.h)	Hp.hr/gal (kW.h/l)	Temp. °F (°C) cool- ing med	Air dry bulb	Barom. inch Hg (kPa)
Maximum Power—21st(2LA) Gear									
98.8 (73.7)	4870 (21.7)	7.61 (12.25)	2008	3	0.434 (0.264)	16.34 (3.22)	189 (87)	79 (26)	29.7 (100.6)
75% of Pull at Maximum Power—21st(2LA) Gear									
69.6 (51.9)	3040 (13.5)	8.58 (13.81)	2232	2	0.531 (0.323)	13.39 (2.64)	189 (87)	77 (25)	30.0 (101.6)
50% of Pull at Maximum Power—21st(2LA) Gear									
46.9 (35.0)	2020 (9.0)	8.71 (14.03)	2250	1	0.654 (0.398)	10.86 (2.14)	189 (87)	77 (25)	30.0 (101.6)
75% of Pull at Reduced Engine Speed—22nd(2LB) Gear									
69.4 (51.8)	2995 (13.3)	8.69 (13.99)	1931	1	0.467 (0.284)	15.19 (2.99)	187 (86)	77 (25)	30.0 (101.6)
50% of Pull at Reduced Engine Speed—22nd(2LB) Gear									
47.3 (35.3)	2025 (9.0)	8.76 (14.09)	1960	1	0.564 (0.343)	12.59 (2.48)	187 (86)	77 (25)	30.0 (101.6)

Location of Test: Groupement d'Antony, Parc de Touvois, BP 44 Antony, France 92163

Dates of Test: December 1997 - September, 1999

Manufacturer: AGCO S.A. Z.A.-No.2 BP 60307, Avenue Blaise Pascal, 60026 Beauvais, France

FUEL and OIL: Fuel No. 2 Diesel Specific gravity converted to 60°/60° F (15°/15°C) 0.853 Fuel weight 7.10 lbs/gal (0.851 kg/l) Oil SAE 10W30 API service classification CD/CE Transmission and hydraulic lubricant BP Terrac Extra 10W/30 Front axle lubricant API GL5 - SAE 85W140

ENGINE: Make Perkins Diesel Type six cylinder vertical with turbocharger Serial No. U623839B Crankshaft lengthwise Rated engine speed 2200 Bore and stroke 3.937" x 5.00" (100.0 mm x 127.0 mm) Compression ratio 16.0 to 1 Displacement 365 cu in (5985 ml) Starting system 12 volt Lubrication pressure Air cleaner two paper elements Oil filter one full flow cartridge Oil cooler engine coolant heat exchanger for crankcase oil, radiator for hydraulic and transmission oil Fuel filter one paper element Muffler underhood Exhaust vertical Cooling medium temperature control thermostat and variable speed fan

CHASSIS: Type 2WD and FWA Serial No. E032005 Tread width rear 60.6" (1538 mm) to 84.1" (2136 mm) front 2WD - 54.3" (1380 mm) to 91.7" (2330 mm), FWA - 61.7" (1566 mm) to 80.9" (2054 mm) Wheelbase 106.3" (2699 mm) Hydraulic control system direct engine drive Transmission selective gear fixed ratio with partial (4) range operator controlled powershift Nominal travel speeds mph (km/h) first 1.30 (2.09) second 1.52 (2.45) third 1.80 (2.90) fourth 2.11 (3.39) fifth 2.22 (3.57) sixth 2.59 (4.17) seventh 2.91 (4.69) eighth 3.06 (4.92) ninth 3.41 (5.49) tenth 3.59 (5.77) eleventh 3.94 (6.34) twelfth 4.03 (6.48) thirteenth 4.62 (7.43) fourteenth 4.71 (7.58) fifteenth 4.88 (7.86) sixteenth 5.45 (8.77) seventeenth 5.72 (9.20) eighteenth 6.38 (10.26) nineteenth 6.74 (10.86) twentieth 7.90 (12.71) twenty-first 8.30 (13.36) twenty-second 9.72 (15.64) twenty-third 10.92 (17.58) twenty-fourth 11.45 (18.45) twenty-fifth 12.79 (20.58) twenty-sixth 13.42 (21.60) twenty-seventh 14.78 (23.79) twenty-eighth 15.09 (24.29) twenty-ninth 17.30 (27.84) thirtieth 17.67 (28.43) thirty-first 20.42 (32.86) thirty-second 23.90 (38.46) reverse 1.22 (1.97), 1.44 (2.31), 1.69 (2.72), 1.98 (3.19), 2.08 (3.35), 2.44 (3.93), 2.74 (4.41), 2.88 (4.63), 3.21 (5.17), 3.37 (5.43), 3.71 (5.97), 3.79 (6.10), 4.34 (6.99), 4.44 (7.14), 4.60 (7.40), 4.97 (8.25), 5.13 (8.65), 6.00 (9.65), 6.34 (10.21), 7.43 (11.95), 7.80 (12.56), 9.13 (14.70), 10.27 (16.53),

DRAWBAR PERFORMANCE

(Unballasted - Front Drive Engaged) MAXIMUM POWER IN SELECTED GEARS

Power Hp (kW)	Drawbar pull lbs (kN)	Speed mph (km/h)	Crank- shaft speed rpm	Slip %	Fuel Consumption lb/hp.hr (kg/kW.h)	Hp.hr/gal (kW.h/l)	Temp. °F(°C) cool- ing med	Air dry bulb	Barom. inch Hg (kPa)
12th(3TC) Gear									
94.4 (70.4)	9690 (43.1)	3.65 (5.88)	2135	10	0.471 (0.287)	15.08 (2.97)	189 (87)	79 (26)	29.7 (100.6)
13th(4TB) Gear									
96.2 (71.7)	8520 (37.9)	4.23 (6.81)	2095	7	0.457 (0.278)	15.53 (3.06)	189 (87)	79 (26)	29.7 (100.6)
14th(3TD) Gear									
97.5 (72.7)	8440 (37.5)	4.33 (6.97)	2093	7	0.455 (0.277)	15.58 (3.07)	190 (88)	79 (26)	29.7 (100.6)
15th(1LA) Gear									
96.7 (72.1)	8150 (36.3)	4.45 (7.16)	2069	6	0.454 (0.276)	15.63 (3.08)	189 (87)	79 (26)	29.7 (100.6)
16th(4TC) Gear									
96.0 (71.6)	7190 (32.0)	5.01 (8.06)	2062	5	0.457 (0.278)	15.53 (3.06)	190 (88)	79 (26)	29.7 (100.6)
17th(1LB) Gear									
97.2 (72.5)	6935 (30.8)	5.26 (8.46)	2058	5	0.448 (0.273)	15.84 (3.12)	190 (88)	79 (26)	29.7 (100.6)
18th(4TD) Gear									
96.6 (72.0)	6140 (27.3)	5.90 (9.49)	2054	4	0.450 (0.274)	15.78 (3.11)	192 (89)	79 (26)	29.7 (100.6)
19th(1LC) Gear									
96.2 (71.7)	5790 (25.8)	6.23 (10.03)	2046	4	0.453 (0.275)	15.68 (3.09)	192 (89)	79 (26)	29.7 (100.6)
20th(1LD) Gear									
98.3 (73.3)	4995 (22.2)	7.38 (11.88)	2049	3	0.443 (0.269)	16.04 (3.16)	192 (89)	79 (26)	29.7 (100.6)
21st(2LA) Gear									
98.8 (73.7)	4870 (21.7)	7.61 (12.25)	2008	3	0.434 (0.264)	16.34 (3.22)	189 (87)	79 (26)	29.7 (100.6)
22nd(2LB) Gear									
98.2 (73.2)	4260 (18.9)	8.64 (13.91)	1980	3	0.433 (0.263)	16.40 (3.23)	189 (87)	79 (26)	29.7 (100.6)
23rd(3LA) Gear									
98.4 (73.4)	3795 (16.9)	9.73 (15.66)	1972	3	0.432 (0.263)	16.45 (3.24)	190 (88)	79 (26)	29.7 (100.6)

10.79 (17.36), 12.02 (19.35), 12.62 (20.31), 13.90 (22.37), 14.20 (22.85), 16.27 (26.19), 16.62 (26.74), 19.21 (30.91), 22.48 (36.18) **Clutch** multiple wet disc operated by foot pedal **Brakes** multiple wet disc hydraulically operated by two foot pedals that can be locked together **Steering** hydrostatic **Power take-off** 540 rpm at 1976 engine rpm or 1000 rpm at 2000 engine rpm **Unladen tractor mass** 2WD - 9600 lb (4355 kg), FWA - 10540 lb (4780 kg)

REPAIRS AND ADJUSTMENTS: No repairs or adjustments

REMARKS: All test results were determined from observed data obtained in accordance with official OECD test procedures. The performance figures on this summary were taken from a test conducted under the OECD Code II test procedure.

NOTE: The data on this summary was obtained from OECD reports 1860 & 1861 conducted on the Massey Ferguson 6270 Diesel (2WD and FWA).

Report reissued: Supplemental sales permit for Challenger MT 535 Diesel, July 2003.

We, the undersigned, certify that this is a true summary of data from OECD Reports No. **1860 & 1861**, Nebraska Summary 303A, June 23, 2003.

Leonard L. Bashford
Director

M.F. Kocher
W.P. Campbell
G.J. Hoffman
Board of Tractor Test Engineers

TRACTOR SOUND LEVEL WITH CAB	Front Wheel Drive	
	2WD dB(A)	Engaged dB(A)
At no load in 14th (3TD) gear	78.0	78.0
Bystander	--	--

Tested Without Ballast

TIRES AND WEIGHT

Rear tires - No., size, ply & psi (kPa)
Front tires - No., size, ply & psi (kPa)
Height of Drawbar
Static Weight with operator - Rear
- Front
- Total

Front Wheel Assist

Two 18.4R38; **, 15 (100)
Two 14.9R28; **, 16 (110)
22.0 in (560 mm)
6160 lb (2795 kg)
4145 lb (1880 kg)
10305 lb (4675 kg)

2WD

Two 18.4R38; **, 15 (100)
Two 11.00-16; 8; 36 (250)
31.5 in (800 mm)
6140 lb (2785 kg)
3625 lb (1645 kg)
9765 lb (4430 kg)

DRAWBAR PERFORMANCE
(Unballasted - 2WD)
FUEL CONSUMPTION CHARACTERISTICS

Power Hp (kW)	Drawbar pull lbs (kN)	Speed mph (km/h)	Crank- shaft speed rpm	Slip %	Fuel Consumption lb/hp.hr (kg/kW.h)	Hp.hr/gal (kW.h/l)	Temp. °F (°C) cool- ing med	Air dry bulb	Barom. inch Hg (kPa)
Maximum Power—21st(2LA) Gear									
99.2 (74.0)	4960 (22.1)	7.50 (12.08)	2019	4	0.434 (0.264)	16.34 (3.22)	189 (87)	77 (25)	29.9 (101.4)
75% of Pull at Maximum Power—21st(2LA) Gear									
68.8 (51.3)	3050 (13.6)	8.46 (13.61)	2234	2	0.520 (0.316)	13.65 (2.69)	189 (87)	73 (23)	29.6 (100.2)
50% of Pull at Maximum Power—21st(2LA) Gear									
46.1 (34.4)	2015 (9.0)	8.58 (13.80)	2249	1	0.625 (0.380)	11.37 (2.24)	189 (87)	73 (23)	29.6 (100.2)
75% of Pull at Reduced Engine Speed—22nd(2LB) Gear									
69.4 (51.8)	3060 (13.6)	8.50 (13.68)	1921	3	0.460 (0.280)	15.43 (3.04)	187 (86)	73 (23)	29.6 (100.2)
50% of Pull at Reduced Engine Speed—22nd(2LB) Gear									
46.7 (34.8)	2040 (9.1)	8.58 (13.81)	1923	2	0.553 (0.336)	12.84 (2.53)	187 (86)	73 (23)	29.6 (100.2)
MAXIMUM POWER IN SELECTED GEARS									
11th(4TA) Gear									
77.8 (58.0)	8455 (37.6)	3.45 (5.56)	2214	15	0.536 (0.326)	13.25 (2.61)	189 (87)	77 (25)	29.9 (101.4)
12th(3TC) Gear									
84.1 (62.7)	8430 (37.5)	3.74 (6.02)	2209	10	0.504 (0.307)	14.09 (2.78)	189 (87)	77 (25)	29.9 (101.4)
13th(4TB) Gear									
93.2 (69.5)	8330 (37.1)	4.20 (6.76)	2152	9	0.479 (0.291)	14.82 (2.92)	191 (88)	77 (25)	29.9 (101.4)
14th(3TD) Gear									
93.5 (69.7)	8185 (36.4)	4.28 (6.89)	2142	9	0.476 (0.290)	14.91 (2.94)	191 (88)	77 (25)	29.9 (101.4)
15th(1LA) Gear									
95.2 (71.0)	8255 (36.7)	4.32 (6.96)	2084	9	0.463 (0.282)	15.33 (3.02)	189 (87)	77 (25)	29.9 (101.4)
16th(4TC) Gear									
96.0 (71.6)	7395 (32.9)	4.87 (7.83)	2045	7	0.451 (0.275)	15.74 (3.10)	187 (86)	77 (25)	29.9 (101.4)
17th(1LB) Gear									
97.2 (72.5)	7105 (31.6)	5.13 (8.26)	2062	7	0.444 (0.270)	15.99 (3.15)	191 (88)	77 (25)	29.9 (101.4)
18th(4TD) Gear									
97.2 (72.5)	6390 (28.4)	5.70 (9.18)	2027	6	0.457 (0.278)	15.53 (3.06)	187 (86)	77 (25)	29.9 (101.4)
19th(1LC) Gear									
97.5 (72.7)	6005 (26.7)	6.09 (9.80)	2036	5	0.446 (0.271)	15.94 (3.14)	189 (87)	77 (25)	29.9 (101.4)
20th(1LD) Gear									
99.0 (73.8)	5210 (23.2)	7.13 (11.47)	2025	5	0.444 (0.270)	15.99 (3.15)	189 (87)	77 (25)	29.9 (101.4)
21st(2LA) Gear									
99.2 (74.0)	4960 (22.1)	7.50 (12.08)	2019	4	0.434 (0.264)	16.34 (3.22)	191 (88)	77 (25)	29.9 (101.4)
22nd(2LB) Gear									
99.1 (73.9)	4285 (19.1)	8.67 (13.95)	1982	3	0.425 (0.259)	16.70 (3.29)	191 (88)	77 (25)	29.9 (101.4)
23rd(3LA) Gear									
98.3 (73.3)	3710 (16.5)	9.94 (16.00)	2013	3	0.432 (0.263)	16.42 (3.24)	191 (88)	77 (25)	29.9 (101.4)

THREE POINT HITCH PERFORMANCE (OECD Static Test)

CATEGORY: II

Quick Attach: None

Maximum Force Exerted Through Whole Range: 7362 lbs (32.7 kN)

i) Opening pressure of relief valve: NA
Sustained pressure of the open relief valve: 2890 psi (199 bar)

ii) Pump delivery rate at minimum pressure and rated engine speed: 29.4 GPM (111.3 l/min)

iii) Pump delivery rate at maximum
hydraulic power: 26.0 GPM (98.8 l/min)
Delivery pressure: 2700 psi (186 bar)
Power: 41.0 HP (30.5 kW)

THREE POINT HITCH PERFORMANCE

Observed Maximum Pressure psi.(bar) 2840(196)
Location: lift cylinder
Hydraulic oil temperature: °F(°C) 149(65)
Location: hydraulic sump
Category: II
Quick attach: none

SAE Static Test—System pressure 2555 psi (176 Bar)

Hitch point distance to ground level in.(mm)	7.9(201)	14.9(378)	21.9(556)	28.9(734)	35.9(912)
Lift force on frame lb	10211	9940	9603	9171	8145
" " " " " (kN)	(45.4)	(44.2)	(42.7)	(40.8)	(36.2)

HITCH DIMENSIONS AS TESTED—NO LOAD

	inch	mm
A	26.9	683
B	11.6	295
C	13.9	354
D	13.0	330
E	7.9	200
F	10.2	260
G	32.3	820
H	1.7	43
I	15.0	382
J	22.1	560
K	21.7	550
L	40.9	1040
M	24.2	615
N	37.0	940
O	7.9	200
P	46.1	1170
Q	36.1	918
R	28.3	719

